



Watch the Rear Engine Rider in action

Data Rates Apply.



RE110

Rear Engine Riders



Tried and True

Some dependable designs are ingeniously simple. Snapper's disc drive transmission uses a spinning plate to power a moveable rubber disc.



Make the Turn

Steering wheel provides more control and tight turning.



Getting Started

Briggs & Stratton® Engines offer the reliability you can count on when mowing the lawn.



Easy-to-Use Design

After 50 years, the rear engine rider has been reinvented to combine tried and true features with today's latest innovation. An easy-to-use design with enhanced features still delivers the same dependability you would expect from a mowing icon.



User-Friendly Controls

Fingertip controls make the rear engine rider simple to drive.

RE100

28" Deck
10.00 ft-lbs Gross Torque*

223cc Briggs & Stratton
1000 Series™ Engine
HI VAC® Mower Deck
Disc Drive Transmission
3-Year Limited Warranty†

RE110

28" Deck
11.5 Gross HP**

344cc Briggs & Stratton
PowerBuilt™ Engine
HI VAC® Mower Deck
Disc Drive Transmission
3-Year Limited Warranty†

RE130

33" Deck
13.5 Gross HP**

500cc Briggs & Stratton
PowerBuilt™ Engine
HI VAC® Mower Deck
Disc Drive Transmission
3-Year Limited Warranty†

RE210

33" Deck
15.5 Gross HP**

500cc Briggs & Stratton
Professional Series™ Engine
HI VAC® Mower Deck
Hydrostatic Transmission
3-Year Limited Warranty†

*All powers levels are stated gross torque at 2600 PM per SAEJ1940 as rated by Briggs & Stratton.

**All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.

†See operator's manual or dealer for complete warranty details. For a full list of specifications, please see page 23.

Attachment listing, please see page 22.

HI VAC®

All rear engine riding mowers come equipped with the HI VAC® Mower Deck. Love to mulch? Add our optional NINJA® Mulching Blade for extra fine mulching.



HI VAC® Mower Deck Similar to a vacuum, the HI VAC® Mower Deck efficiently cuts and sucks up grass clippings for a clean finish. The secret to the cut is the unique blade and rolled deck edge that generates a large volume of air and creates suction.

NINJA® Mulching



Optional NINJA® Mulching Blade Finely mulch your grass with our exclusive NINJA® Blade that features six powerful cutting surfaces. While the blade mulches the grass clippings, the deck design blows them back into the lawn.

An American Classic Reborn.



Model	RE100	RE110	RE130	RE210
Engine				
Brand	Briggs & Stratton 1000 Series™ OHV	Briggs & Stratton PowerBuilt™ OHV	Briggs & Stratton PowerBuilt™ OHV	Briggs & Stratton Professional Series™ OHV
Gross Torque*	10.00 ft-lbs	N/A	N/A	N/A
Gross Horsepower** / Cylinders	N/A / 1	11.5 / 1	13.5 / 1	15.5 / 1
Engine Displacement (cc)	223	344	500	500
Starter	Electric	Electric	Electric	Electric
Choke / Throttle	Single-Lever	Single-Lever	Single-Lever	Single-Lever
Fuel Tank Capacity (U.S. Gallons)	2	2	2	2
Battery (cca)	35	190	190	190
Transmission				
Transmission Type	6-Speed, Disc Drive	8-Speed, Disc Drive	8-Speed, Disc Drive	Hydro-Gear® T2®, Hydrostatic
Speed Control Design	Gear Shift Lever	Gear Shift Lever	Gear Shift Lever	Foot Pedals
Speed - Fwd / Rev (mph)	1 - 4.5 / 0 - 1.9	1 - 4.5 / 0 - 1.9	1 - 4.5 / 0 - 1.9	0 - 5 / 0 - 2
Brake	Friction	Friction	Friction	Friction
Chassis				
Frame	12-Gauge Steel	12-Gauge Steel	12-Gauge Steel	12-Gauge Steel
Front Axle	Welded Steel, Pivoting	Welded Steel, Pivoting	Welded Steel, Pivoting	Welded Steel, Pivoting
Front Tires (inches)	11	11	11	13
Rear Tires (inches)	16	16	16	16
Seat	9" Low-back, Adjustable	11" Mid-back, Adjustable	11" Mid-back, Adjustable	11" Mid-back, Adjustable
Mower Deck				
Cutting Width (inches)	28	28	33	33
Number of Blades	1	1	1	1
Deck Type	HI VAC®	HI VAC®	HI VAC®	HI VAC®
Height-of-Cut Range (inches)	1.5 - 4	1.5 - 4	1.5 - 4	1.5 - 4
Height-of-Cut Positions	6	6	6	6
Blade Engagement	Manual Lever	Manual Lever	Manual Lever	Manual Lever
Mower Deck Lift	Mechanical	Mechanical	Mechanical	Mechanical
Deck Suspension	Frame Hung	Frame Hung	Frame Hung	Frame Hung
Deck Thickness	13-Gauge	13-Gauge	13-Gauge	13-Gauge
Spindles	Steel	Steel	Steel	Steel
Features				
Steering	Wheel	Wheel	Wheel	Wheel
Headlights	No	Optional	Optional	Yes
Key Start	Yes	Yes	Yes	Yes
Cup Holder	Yes	Yes	Yes	Yes
Dimensions				
Length x Width x Height (inches)	66 x 32 x 43	66 x 32 x 43	66 x 37 x 43	66 x 37 x 43
Limited Warranty				
Residential†	3-year	3-year	3-year	3-year
Commercial†	90-day	90-day	90-day	90-day

*All power levels are stated gross torque at 2600 RPM per SAE J1940 as rated by Briggs & Stratton.

**All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.

†See operator's manual or dealer for complete warranty details. Length of engine warranty coverage varies by manufacturer.

We reserve the right to change specifications, features and pricing without notice. Product may vary from images shown.

Attachment & Accessory Guide

SELECT LAWN TRACTOR & ZERO TURN ATTACHMENTS & ACCESSORIES

Model	Rear Engine Rider	SPX™ Series	200Z	285Z	300Z	400Z	550Z
Arm Rest Kit			•	•	•	•	•
Dethatcher, Tow-Behind, 40"		•					
Dump Cart	•	•	•	•	•	•	•
Fast-Vac® Twin Collector						•	
Flat Free Castor Tire Assembly						•	•
Front Double Bar Bumper		•					
Grass Mulching Kits		•	•	•	•	•	•
Grass Striping Kit						•	•
Light Kit	•					•	•
Rear Hitch Kit						•	•
Single Bag Catcher	•						
Single-Stage Snowthrower, 42"		•					
Snow Blade, 42"		•					
Snow Cab (Soft-Sided)		•					
Tiller, Tow-Behind 36"		•					
Tire Chains		•					
Tractor Cover	•	•					
Triple Catcher*			46"	52"			52", 61"
Turbo-Pro™ Collection System						•	
Twin Catcher	•	42"	42"				
Weight Carrier, Front		•					
Weight Carrier, Rear		•					
Weight, Front Counter		•					
Weight, Rear Wheel		•					
Weight, Suitcase		•					

*Collection systems are available with or without a turbo. Some systems may require a turbo.

Note: Attachments for prior year models and additional attachments or accessories not shown may be available.

Some attachments require additional installation components (i.e. front weights for a catcher). Please see dealer for details.