



440 TRACTOR

BOLDER. BETTER. STRONGER. STEINER.



More Powerful
Engine Choices
More Hydraulic Power
Stronger Front and
Rear Transaxles
New Optional Accessories

Easier Operation
More Comfort
Easily and Completely
Versatile
More Standard Features

440 TRACTOR SPECIFICATIONS

MODELS 440-34KO, 440-40KO, 440-25KDL, 440-32KGL



Dimensions:

Overall Width: 44.5", 66.5" with dual wheels
 Overall Length: 86" with ROPS up
 Overall Height: 73.25" with ROPS up
 50" with ROPS folded
 Wheelbase: 43.5"
 Minimum Ground Clearance: 4.75"
 Frame Oscillation: 8"
 Frame Articulation: 36 degrees, 44" turning radius

Hydraulics:

Pump: Eaton Series 26
 Total Capacity (gpm): 6 gpm @ 3600 RPM
 Lift Pressure: 1500 PSI
 Hydraulic Oil Capacity: 5 US Gallons

Transmission:

Drive Train: Eaton model 70160, Radial Axle Piston Pump
 Transaxles: Peerless 2600 Dual Range
 Speeds: 0-10.5 MPH, High; 0-5.25 MPH, Low
 Steering: Hydraulic Power Steering
 Brakes: Dry Disc Type

Attachment Drive:

Front PTO Clutch: Electric Warner Mag Stop 225 Ft. Lb w/ Midpole Brake
 Hydraulic Outlets: Quick Couplers-Front

Fuel System:

8 US Gallon Tank Capacity

Wheels:

38 Special (Fieldtrax) 22x12-10
 Mag Off Road (Bar) 22x12-10
 Lightfoot (Turf) 22x11-10

Hitch:

Front: Steiner Quick-Hitch, with standard front release control or optional release from seated position
 Back: Standard 2" receiver hitch, with optional category 1 three-point hitch

High-Back Bucket Seat:

Armrests: standard
 Suspension: Radial Bearing Suspension, optional Mechanical Suspension
 Adjustment: 7" Fore and Aft

Additional Features:

Lighting: 200 watt halogen quartz headlights (4-50 each), rear marker running lights
 Tool Box: Standard
 Cup Holder: Standard
 PTO Tension Adjustment: Manual
 12 Volt Outlet: Optional, Mid

MODEL SPECIFICATIONS

Models	440-34KO	440-40KO	440-25KDL	440-32KGL
Weight:	1489	1489	1517	1517
Engine:	Kohler® Command Pro CH904, Air-Cooled	Kohler® Command Pro CH1000, Air-Cooled	Kubota® D902, Diesel LC	Kubota® WG972, Gas LC
HP @ RPM*:	34 HP gross @ 3600 RPM	40 HP gross @ 3600 RPM	24.8 (gross intermittent) @ 3600 RPM	32.4 (gross intermittent) @ 3600 RPM
Engine Cyls & Displacement:	2 cyl, 999cc (61 cu. in.)	2 cyl, 999cc (61 cu. in.)	3 cyl, 898cc (54.8 cu. in.)	2 cyl, 962cc (58.7 cu. in.)
Alternator/Amps:	40 Amp	40 Amp	40 Amp	40 Amp
Battery/Cold Cranking Amps:	12V - 525 Cold Cranking Amps	12V - 525 Cold Cranking Amps	12V - 630 Cold Cranking Amps	12V - 525 Cold Cranking Amps
Standard Instrumentation:	Tachometer Hour Meter Low Oil Pressure Indicator Voltmeter Parking Brake PTO Switch Driving Lights Switch	Tachometer Hour Meter Low Oil Pressure Indicator Voltmeter Parking Brake PTO Switch Driving Lights Switch	Tachometer Hour Meter Engine Coolant Temp Low Oil Pressure Indicator Voltmeter Glow Plug Light Parking Brake PTO Switch Driving Lights Switch	Tachometer Hour Meter Engine Coolant Temp Low Oil Pressure Indicator Voltmeter Parking Brake PTO Switch Driving Lights Switch

* Engine HP is per SAE ratings for Kubota Per SAE-1939; Kohler Per SAE-1940.
 Steiner uses commercial-strength engine options for longevity and ease of service. All engines are warranted by their respective manufacturer and your local dealer. The power engine ratings are provided by the engine manufacturer. Actual power output is dependent on many factors including engine rpm, air density and engine condition.



All Steiner products are made with pride in the U.S.A. and are warranted commercially for 2 years. Please see your local dealer for full warranty details also found in the product manual. Your safety is important to us. Before operating any turf maintenance equipment, consult your operator's manual for safe operating and maintenance procedures.

For more information about Steiner products, visit your Steiner dealer today.
 For the location of the dealer nearest you, call 1-866-469-1242 or 1-920-699-2000.
 Visit us on the Web at www.steinerturf.com and visit YouTube to see the Steiner 440 Play in the Snow.

H.E.R.S. INC.
 1203 S. PARKER
 KS 66061
 United States
cathy@hersinc.net
www.hersinc.net



Steiner® is a registered trademark of Schiller Grounds Care, Inc.
 ©2012 Schiller Grounds Care, Inc. Company. All rights reserved. Steiner | One BOB-CAT Lane | Johnson Creek, WI 53038